

Precision Linear Motion Platform

FEATURES

- Compact Low-Profile Design
- 100mm Travel
- Zero backlash, precision ground ball screws
- Optical limit switches with home
- Stepper motor drive
- Crossed Roller Bearings



The LNS-BS Series stages are designed for a variety of applications. This compact low profile ball screw stage is built for high duty cycles and long life for factory automation and semiconductor processing equipment. This stage has exceptional levels of accuracy, repeatability, flatness and straightness. The crossed roller bearings and a precision ground ball screw offer extremely smooth operation and velocity control. The LNS-BS Series stages can be stacked to create X, Y and Z motion. The stage can operate in any orientation.




LNS-100-BS-B-N-S-0-00

Motion Specifications

Product Specifications




Force X (N)	200
Force Y (N)	250
Force Z (N)	500
Flatness (μm)	5
Height (mm)	45
Length (mm)	260
Limit Switches	Yes
Linear Accuracy (μm)	17
Linear Repeatability (μm)	2
Linear Velocity (mm/s)	25
Moment X (N-m)	60
Moment Y (N-m)	275
Moment Z (N-m)	110
Moving Mass X (kg)	1.67
Pitch +/- (arc-sec)	10
Screw Lead (mm)	2
Stage Mass (kg)	3.67
Stepper Motor Resolution (Whole Steps/rev)	400
Straightness (μm)	5
Width (mm)	153
Yaw +/- (arc-sec)	10




LOAD DIRECTIONS

Part Number Description

LNS	LNS Series
100	100mm Travel
BS	Ball Screw Drive
B	Stepper Motor
N	Limit and Home Switch Only
S	Standard Precision
0	No Additional Options
00	Standar Product (Call for custom)



Feedback Connector (DSUB26HD MALE)	
PIN	NAME
1	+5V
2	*
3	*
4	*
5	LIM+
6	*
7	*
8	*
9	*
10	*
11	*
12	*
13	*
14	LIM-
15	*
16	*
17	*
18	*
19	GND
20	*
21	*
22	*
23	HOME
24	*
25	*
26	*
* Reserved	



Motor Connector (DSUB9 MALE)	
PIN	NAME
1	*
2	*
3	*
4	*
5	*
6	PHASE A+
7	PHASE A-
8	PHASE B+
9	PHASE B-
* Reserved	



LNS-100-BS-B-N-S-0-00

Electrical Specifications

Motor Specifications	
Motor Type	Bipolar Stepper
Current/phase (A)	0.8
Resistance/phase (Ω)	10.0
Induction/phase(mH)	6.9

Feedback Specifications	
Supply Voltage (V)	5.0 $\pm$ 10%
Supply Current (mA)	250
Encoder Feedback	No
Limit Switches	Yes
Limit Switch Output Type	CMOS
Limit Switch Output current (mA)	$\pm$ 20.0
Home Switch	Yes
Home Switch Output Type	CMOS
Home Switch Output current (mA)	$\pm$ 20.0

A home switch is provided near center mechanical travel and a limit switch at each end of travel. The limit switches will be pulled low throughout the travel range of the stage. The output will swing high at the end of travel and remain high until the mechanical limit is reached.